



# JOURNEY

5', 6' & 7' Wide  
Cargo Trailers

Specifications vary by plant



Optional Wedge Front Shown



## Standard Features

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 24" O.C. Roof Bows
- Spring Axles
- EZ-Lube Hubs
- 4-Wheel Electric Brakes (Tandem Axle)
- 15" Radial Tires
- 2" Coupler (Single Axle)
- 2-5/16" Coupler (Tandem Axle)
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- 18" Wedge (Flat Top)
- Radius Front (Round Top)
- TPO Front Cap (Round Top)
- .030 Top Wrap (Round Top)
- Aluminum Exterior
- 1 Piece Aluminum Roof
- Aluminum Fenders
- 24" Stoneguard
- Ramp Door w/ Spring Assist or Single Rear Door on 5' Wides
- Ramp Door w/ Spring Assist or Double Rear Doors on 6' & 7' Wides
- 32" Door w/ Flushlock & Metal Holdbacks on 6' & 7' Wide Models
- (2) Sidewall Vents
- 4-Way Plug (Single Axle)
- 7-Way Plug (Tandem Axle)
- LED Tail Lights
- LED Clearance Lights
- (1) Dome Light w/ Switch
- Moisture Barrier (IN & UT)
- Automotive Undercoating
- Limited 3 Year Warranty

	<b>JOURNEY CARGO SERIES</b>					
	JV5X8SI2	JV5X10SI2	JV6X10SI2	JV6X12SI2	JV7X14TE2	JV7X16TE2
Overall Length	12'	14'1"	14'1"	16'3"	18'6"	20'6"
Width	82"	82"	93"	93"	102"	102"
Height	84"	84"	91"	91"	92"	92"
Interior Length	9'4"	11'4"	11'4"	13'4"	15'4"	17'4"
Interior Width	56"	56"	68"	68"	78 1/2"	78 1/2"
Interior Height	66"	66"	72"	72"	72"	72"
Platform Height	18"	18"	18"	18"	19"	19"
Rear Opening Ht.	60"	60"	66"	66"	66"	66"
Rear Opening Wd.	51"	51"	66"	66"	76 1/2"	76 1/2"
Hitch Ball Height	16"	16"	16"	16"	16"	16"
Hitch Ball Size	2"	2"	2"	2"	2 5/16"	2 5/16"
Brakes	OPT	OPT	OPT	OPT	ELECTRIC	ELECTRIC
GVWR	2990#	2990#	2990#	2990#	7000#	7000#
Hitch Weight	128#	119#	163#	172#	234#	265#
Curb Weight	1070#	1080#	1360#	1440#	2050#	2210#
Payload Capacity	1920#	1910#	1630#	1550#	4950#	4790#
Tires	15"	15"	15"	15"	15"	15"
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance
Tail Lights	LED	LED	LED	LED	LED	LED
Clearance Lights	LED	LED	LED	LED	LED	LED
Dome Light	STD	STD	STD	STD	STD	STD
Switch	STD	STD	STD	STD	STD	STD
Sidewall Vents	2	2	2	2	2	2
Stone Guard	24"	24"	24"	24"	24"	24"
Round Front*	OPT	OPT	OPT	OPT	OPT	OPT
Side Door	OPT	OPT	32"	32"	32"	32"
Rear Door	SINGLE / RAMP	SINGLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP
Sand Pad	STD	STD	STD	STD	STD	STD
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Crossmembers	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive

\*For Round Top Dimensions Please Refer to the CargoSport Literature

Specifications Subject to Change Without Notice