



## **WHITEOUT**

8.5' Wide Aluminum  
Snowmobile/ATV Trailer

Specifications vary by plant



## Standard Features

Optional Equipment May Be Shown

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 16" O.C. Roof Bows
- Spring Axles w/EZ-Lube Hubs
- Electric Brakes w/ Breakaway & Battery Box
- 15" Radial Tires
- 2" Coupler
- Safety Chains
- Single Tube Tongue
- Swing-up Jack w/Dolly Wheel
- 3/4" High Performance Floor
- 24" H High Performance Kickplate
- Aluminum Exterior
- 24"H ATP Exterior Lower Bottom Panels
- 1 Piece Aluminum Roof
- 24" Stoneguard
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door with Spring Assist
- 7-Way Plug
- LED Tail and Clearance Lights
- (1) LED Dome Light
- Transport Canada Certified Tie Downs
- Limited 3 Year Warranty

	<b>ALUMINUM WHITEOUT SNOWMOBILE TRAILER</b>	
	APWFT 85X12 SE2	APWFT 85X14 SE3
Overall Length	239"	263"
Width	101"	101"
Height	95"	95"
Interior Length	167"	191"
Interior Width	96"	96"
Interior Height	66"	66"
Platform Height	25"	26"
Rear Opening Height	62"	62"
Rear Opening Width	94"	94"
Hitch Ball Height	22"	23"
Hitch Ball Size	2"	2"
Front Ramp Open Height	62"	62"
Front Ramp Open Width	50"	50"
Brakes	ELECTRIC	ELECTRIC
GVWR	3500#	5200#
Hitch Weight	180#	205#
Curb Weight	1700#	1850#
Payload Capacity	1800#	3350#
Tires	ST205/75R15	ST225/75R15
Wheels	SILVER MOD	SILVER MOD
Frame	TUBE	TUBE
Sidewalls	24"H High Performance Kick Plate	24"H High Performance Kick Plate
Floor	3/4" High Performance	3/4" High Performance
Ceiling	OPT	OPT
Tail Lights	LED	LED
Clearance Lights	LED	LED
LED Dome Light	1	1
Sidewall Vents	STD	STD
Stone Guard	STD	STD
V-Nose	STD	STD
Side Door	OPT	OPT
Tie Downs	6	6
Dolly Wheel	STD	STD
Side Posts	16"	16"
Roof Bows	16"	16"
Crossmembers	24" O.C.	24" O.C.
Axle	Spring	Spring
EZ Lube	YES	YES

Specifications Subject to Change Without Notice