

EDGE® ALX RACE TRAILERS

Haulmark®

**WHEN SECOND
BEST ISN'T
GOOD ENOUGH!**

You love your car . . . the best engine, the best tires, the best brakes. Haulmark® has an all-aluminum race trailer that lives up to your exacting standards.

The EDGE® ALX!



Trailers shown may feature optional equipment available at an additional charge.

THE EDGE® ALX
ALL ALUMINUM

SPECIFICATIONS

THE EDGE[®] ALX
ALL ALUMINUM

	EGALX8520T3	EGALX8524T3	EGALX8528T4	EGALX8532R4
Body: Length Width	20' 0" 8' 4"	24' 0" 8' 4"	28' 0" 8' 4"	32' 0" 8' 4"
Overall: Length Width Height	24' 6" 8' 6" 8' 9"	28' 6" 8' 6" 8' 9"	32' 6" 8' 6" 8' 10"	36' 6" 8' 6" 8' 10"
Interior: Length Width Height	19' 8" 8' 2" 6' 10"	23' 8" 8' 2" 6' 10"	27' 8" 8' 2" 6' 10"	31' 8" 8' 2" 6' 10"
Width Between Wheel Boxes	80"	80"	80"	80"
Height of Wheel Box from Floor	10"	10"	11.25"	11.25"
Platform Height	21"	21"	22"	22"
Torflex [®] Suspension E-Z Lube [®] Axles: Qty	Tandem	Tandem	Tandem	Triple
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 D	ST225/75R15 E	ST235/85R16 E	ST235/85R16 E
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	21"	21"	22"	22"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GWR	9,990 lbs.	9,990 lbs.	12,000 lbs.	18,000 lbs.
Curb Weight (Approximate)	3,400 lbs.	3,800 lbs.	4,600 lbs.	6,350 lbs.
Payload Capacity (Approximate)	6,590 lbs.	6,190 lbs.	7,400 lbs.	11,650 lbs.
Rear Ramp Door Opening - Width x Height	96" x 80"	96" x 80"	96" x 80"	96" x 80"
12v Male Connection	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 6"	2" x 6"	2" x 6"	2" x 6"
Beavertail	24"	48"	48"	48"

STANDARD FEATURES

- Flat Front/Flat Roof Design
- All-Aluminum Frame Construction
- Aluminum Door Holdback
- Fully Integrated, All Tube, Roof, Sidewall and Chassis Design
 - 16" OC Floor Crossmembers
 - 16" OC Wall Posts
 - 16" OC Roof Framing
- 54" A-Frame with Center Drawbar
- 8,000 lb. Side Wind Drop Leg Jack
- .080 ACP Panels (*Select Colors*)
- Bright Polished Aluminum Cap and Stainless Steel Front Corners
- Bright Polished Aluminum Rear Corners and Header
- Wide Extruded Aluminum Top and Bottom Trim
- 1-Piece Aluminum Roof
- 24" ATP Stonguard
- Spring-Assisted Rear Ramp Door with 96" Opening
- Heavy-Duty Recessed Ramp Door Paddle Latches
- 36" Side Entry Door with Flush Lock
- Spread Torflex[®] Axles with Skirting and Aluminum Fenderettes
- Goodyear[®] Radial Tires with Aluminum Wheels
- Mid-Ship Amber Marker/Turn Lights
- 12v LED Smoked Lens Clearance Lights
- 12v LED Smoked Lens Slim Line Tail/Turn/Backup Lights (3 pair)
- 12v LED Dome Lights (4) with Illuminated Interior Wall Switch (1)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" FlexCore[™] Flooring
- 3/8" FlexCore[™] Sidewall Liner
- Luan Ceiling Liner
- 3-Year Limited Warranty



*Trailers feature optional equipment available at additional charge.

