

EDGE® ALX STACKER TRAILERS

Haulmark

WHEN RACING BECOMES MORE THAN A HOBBY

Are you ready for the big time? Then take a look at the EDGE® ALX Stacker trailers, designed for the motorsports professional and serious recreational enthusiast. Not only are EDGE® ALX Stackers large enough to haul multiple vehicles, but they have enough storage space for spare parts, tools and diagnostic equipment.



Trailers shown may feature optional equipment available at an additional charge.

THE EDGE® ALX
ALL ALUMINUM

SPECIFICATIONS

THE EDGE[®] ALX
ALL ALUMINUM

		EGALX8524R4-S	EGALX8524R5-S	EGALX8528R5-S	EGALX8532R5-S
Body:	Length Width	24' 0" 8' 4"	24' 0" 8' 4"	28' 0" 8' 4"	32' 0" 8' 4"
Overall:	Length Width Height	29' 0" 8' 6" 13' 5"	29' 0" 8' 6" 13' 5"	33' 0" 8' 6" 13' 5"	37' 0" 8' 6" 13' 5"
Interior:	Length Width Height	23' 8" 8' 1" 11' 3"	23' 8" 8' 1" 11' 3"	27' 8" 8' 1" 11' 3"	31' 8" 8' 1" 11' 3"
Width Between Wheel Boxes		81"	81"	81"	81"
Platform Height		25"	25"	25"	25"
Auto Lift Length		13' 0"	13' 0"	16' 0"	16' 0"
Auto Lift Height		6' 8"	6' 8"	6' 8"	6' 8"
Torflex[®] Suspension E-Z Lube[®] Axles: Qty		Triple	Triple	Triple	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16
Tire Load Range		E	E	E	E
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		23"	23"	23"	23"
Hitch Weight (% of Curb Weight)		10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR		18,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.
Curb Weight (Approximate)		7,600 lbs.	8,750 lbs.	9,600 lbs.	10,700 lbs.
Payload Capacity (Approximate)		10,400 lbs.	12,250 lbs.	11,400 lbs.	10,300 lbs.
Rear Ramp Door Opening - Width x Height		92" x 96"	92" x 96"	92" x 96"	92" x 96"
Side Double Door Opening - Width x Height		48" x 72"	48" x 72"	60" x 78"	60" x 78"
12v Male Connection		7-way	7-way	7-way	7-way
Tube Main Rails		2" x 8"	2" x 8"	2" x 8"	2" x 8"

STANDARD FEATURES

- Polished Aluminum Front Cap & Stainless Steel Front Corners
- 1-Piece Aluminum Roof
- .080 ACP Panels (*Select Colors*)
- Torflex[®] Spread Axles with Drop Skirting
- 24" ATP Stoneguard
- 8-Bolt 16" Goodyear Radial Tires with Silver Viper Aluminum Wheels
- 2-5/16" Adjustable Height Coupler with Steel Boot (25,000 lbs.)
- 12K Single Leg Hydraulic Landing Gear
- 12v LED 24" 9K Lumen Scene Lights (4)
- 3/4" PlexCore[™] Decking with Black Coin Rubber Floor Covering
- 3/8" PlexCore[™] Sidewall Liner with .030 White Aluminum Covering
- White Aluminum Ceiling Liner
- Cabinets: L-Shaped Base, Overhead and Generator Compartment
- Steel Car Hoist system with 36" Extension
- Attic with Ladder Access* (6' 6" from Floor) *28' & 32' Models only
- 36" Aluminum Ramp Extension with Large Bumpers
- Generator Compartment with Access Door
- Air Compressor Prep Package — Hose, 4 Coupling and 120V Receptacle
- 120/240v 50 amp Motorbase Receptacle with Twist Lock Connect
- Battery Disconnect Switch
- 12v LED 36" Slim Line White Area Accent Lights (8)
- 12v LED 6" Round Dome Lights (4)
- 16" OC Tube Crossmembers
- 16" OC Tube Vertical Posts
- 16" OC Tube Roof Structure
- Premium Side Double Door with 40"W Slide out Step
- D-Ring Tie-Downs with Welded Plates (4)
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at an additional charge.

