

WELLS  
CARGO®

# MOTORTRAC® RACE TRAILERS OUR FLAGSHIP MOTOSPORTS TRAILER

## PERFORMANCE THAT'S TRUE TO FORM!

The MotorTrac® Race Trailer from Wells Cargo® is all about delivering performance.

Performance on the road . . .  
Performance at the track . . .  
Performance year after year.

Successful racers are constantly searching for superior performance, it makes sense to use top-notch equipment like the flagship MotorTrac® Racing Trailer.



Trailers shown may feature optional equipment available at an additional charge.

**MOTORTRAC®**

# SPECIFICATIONS



	MT8520T3	MT8524T3	MT8528T4	MT8532R4
<b>Body:</b> Length Width	20' 0" 8' 4"	24' 0" 8' 4"	28' 0" 8' 4"	32' 0" 8' 4"
<b>Overall:</b> Length Width Height (to top of roof vent)	24' 7" 8' 6" 9' 1"	28' 7" 8' 6" 9' 1"	32' 7" 8' 6" 9' 3"	36' 7" 8' 6" 9' 3"
<b>Interior:</b> Length Width Height	19' 8" 8' 1" 6' 10"	23' 8" 8' 1" 6' 10"	27' 8" 8' 1" 6' 10"	31' 8" 8' 1" 6' 10"
<b>Width Between Wheel Boxes</b>	83"	83"	83"	83"
<b>Height of Wheel Box from Floor</b>	10"	10"	10"	10"
<b>Platform Height at Beavertail</b>	19"	19"	21"	21"
<b>Torflex® Suspension E-Z Lube® Axles: Qty</b>	Tandem	Tandem	Tandem	Triple
<b>Brakes with Breakaway Kit</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size</b>	ST225/75R15	ST225/75R15	ST235/85R16	ST235/85R16
<b>Tire Load Range</b>	E	E	E	E
<b>Hitch Ball Size</b>	2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	20"	20"	22"	22"
<b>Hitch Weight (% of Curb Weight)</b>	10% to 15%	10% to 15%	10% to 15%	10% to 15%
<b>GVWR</b>	9,990 lbs.	9,990 lbs.	12,000 lbs.	18,000 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>	96" x 78"	96" x 78"	96" x 78"	96" x 78"
<b>12v Male Connection</b>	7-way	7-way	7-way	7-way
<b>Tube Main Rails</b>	2" x 6"	2" x 6"	2" x 8"	2" x 8"
<b>Beavertail</b>	32"	48"	72"	72"

## STANDARD FEATURES

- Flat Front/Flat Roof Truck-Body Design
- Roof and Sidewall Structure
  - 16" OC C-Channel Floor Crossmembers
  - 16" OC Tube Sidewall Posts
  - 16" OC Tube Roof Structure
- 54" A-Frame with Center Tube
- Skid Pads on Rear Corners
- No-Show Beavertail
- 2<sup>5/16</sup>" Adjustable Wallace Forge® 20K Cast Coupler (Made in the USA)
- Square Tube 8K Drop Leg Side Wide Jack with Footplate (Bolt-On/Replaceable)
- .080 ACP Panels (Select Colors)
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Polished Aluminum Rear Corners and Header
- 1-Piece Aluminum Roof
- ArmorTech® on A-Frame and Rear End Rail
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 96"W Opening & 16" PlexCore Ramp Extension
- Heavy-Duty Recessed Paddle Latches on Rear Ramp Door
- 36" x 78" Side Entry Door with Recessed Step
- Spread Torflex® Axle Design with Drop Skirting
- Goodyear® Radial Tires with Black Aluminum Wheels
- 12v Smoke Lens LED Exterior Clearance Lights
- 12v Smoke Lens Slim Line Stop/Tail/Turn/Back-Up Lights (3 pr.)
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore™ High Performance Decking
- 3/8" PlexCore™ High Performance Sidewall Liner
- Economy Ceiling Liner
- 3-Year Limited Warranty



Turbopackage with additional optional equipment available at additional cost.

