

WELLS
CARGO®

MOTORTRAC® SS ALUMINUM RACE TRAILERS

NEVER SETTLE FOR SECOND PLACE

Racing is your passion and your race car is one of your most prized possessions. Short cuts are never an option. So why would you ever consider hauling your car to the track in anything other than the Wells Cargo® MotorTrac® SS? You haven't invested this much into your car and your passion to risk settling for second best now. Choose the best.

The New MotorTrac® SS!



Trailers shown may feature optional equipment available at an additional charge.

MOTORTRAC®
SS

SPECIFICATIONS

		MTSS8520T3	MTSS8524T3	MTSS8528T4	MTSS8532R4
Body:	Length Width	20' 0" 8' 4"	24' 0" 8' 4"	28' 0" 8' 4"	32' 0" 8' 4"
Overall:	Length Width Height	24' 6" 8' 6" 8' 9"	28' 6" 8' 6" 8' 9"	32' 6" 8' 6" 8' 10"	36' 6" 8' 6" 8' 10"
Interior:	Length Width Height	19' 8" 8' 2" 6' 10"	23' 8" 8' 2" 6' 10"	27' 8" 8' 2" 6' 10"	31' 8" 8' 2" 6' 10"
Width Between Wheel Boxes		80"	80"	80"	80"
Height of Wheel Box from Floor		10"	10"	11.25"	11.25"
Platform Height		19"	19"	20"	20"
Torflex® Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	Tire Load Range	ST225/75R15 E	ST225/75R15 E	ST235/85R16 E	ST235/85R16 E
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		21"	21"	22"	22"
Hitch Weight (% of Curb Weight)		10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR		9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
Rear Ramp Door Opening - Width x Height		96" x 80"	96" x 80"	96" x 80"	96" x 80"
12v Male Connection		7-way	7-way	7-way	7-way
Tube Main Rails		2"x 6"	2"x 6"	2"x 6"	2"x 6"
Beavertail		24"	48"	48"	48"

STANDARD FEATURES

- Flat Front/Flat Roof Design
- All-Aluminum Frame Construction
- Aluminum Door Holdback
- Fully Integrated, All Tube, Roof, Sidewall and Chassis Design
 - 16" OC Floor Crossmembers
 - 16" OC Wall Posts
 - 16" OC Roof Framing
- 54" A-Frame with Center Drawbar
- 8,000 lb. Side Wind Drop Leg Jack
- .080 ACP Panels (Select Colors)
- Bright Polished Aluminum Cap and Stainless Steel Front Corners
- Bright Polished Aluminum Rear Corners and Header
- Wide Extruded Aluminum Top and Bottom Trim
- 1- Piece Aluminum Roof
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 96" Opening
- Heavy-Duty Recessed Ramp Door Paddle Latches
- 36" Side Entry Door with Flush Lock
- Spread Torflex® Axles with Skirting and Aluminum Fenderettes
- Goodyear® Radial Tires with Aluminum Wheels
- Mid-Ship Amber Marker/Turn Lights
- 12v LED Smoked Lens Clearance Lights
- 12v LED Smoked Lens Slim Line Tail/Turn/Backup Lights (3 pair)
- 12v LED Dome Lights (4) with Illuminated Interior Wall Switch (1)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" FlexCore™ Flooring
- 3/8" FlexCore™ Sidewall Liner
- Ceiling Liner
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at additional charge.