



**WELLS
CARGO®**

MOTORTRAC® SS STACKER ALUMINUM STACKER TRAILERS

WHEN RACING IS MORE THAN A HOBBY

Has your part-time hobby become something more serious? Then check out the MotorTrac® SS Stacker trailers from Wells Cargo®. These trailers have been designed for the motorsports professional and serious recreational enthusiast. The MotorTrac SS Stackers are large enough to haul multiple vehicles, along with affording plenty of space to store spare parts, tools, diagnostic equipment, and more!



Trailers shown may feature optional equipment available at an additional charge.

MOTORTRAC®

SPECIFICATIONS

MOTORTRAC

		MTSS8524R4-S	MTSS8524R5-S	MTSS8528R5-S	MTSS8532R5-S
Body:	Length	24' 0"	24' 0"	28' 0"	32' 0"
	Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	Length	29' 0"	29' 0"	33' 0"	37' 0"
	Width	8' 6"	8' 6"	8' 6"	8' 6"
	Height	13' 5"	13' 5"	13' 5"	13' 5"
Interior:	Length	23' 8"	23' 8"	27' 8"	31' 8"
	Width	8' 1"	8' 1"	8' 1"	8' 1"
	Height	11' 3"	11' 3"	11' 3"	11' 3"
Width Between Wheel Boxes		81"	81"	81"	81"
Platform Height at Beavertail		25"	25"	25"	25"
Auto Lift Length		13' 0"	13' 0"	16' 0"	16' 0"
Auto Lift Height		6' 8"	6' 8"	6' 8"	6' 8"
Torflex® Suspension EZ-Lube® Axles: Qty		Triple	Triple	Triple	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16	
Tire Load Range	E	E	E	E	
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	
Hitch Height to Top of Ball	23"	23"	23"	23"	
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%	
GVWR	18,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	
Curb Weight (Approximate)	7,600 lbs.	8,750 lbs.	9,600 lbs.	10,700 lbs.	
Payload Capacity (Approximate)	10,400 lbs.	12,250 lbs.	11,400 lbs.	10,300 lbs.	
Rear Ramp Door Opening - Width x Height	92" x 96"	92" x 96"	92" x 96"	92" x 96"	
Side Double Door Opening - Width x Height	48" x 72"	48" x 72"	60" x 78"	60" x 78"	
12v Male Connection	7-Way	7-Way	7-Way	7-Way	
Tube Main Rails	2" x 8"	2" x 8"	2" x 8"	2" x 8"	

STANDARD FEATURES

- Polished Aluminum Front Cap
- Stainless Steel Front Corners
- 1-Piece Aluminum Roof
- .040 Bonded Aluminum Exterior (Smooth Appearance)
- Spread Torflex Axles with Drop Skirting
- 24" ATP Stonguard
- 8-Bolt 16" Goodyear Radial Tires with Black Aluminum Wheels
- 2-5/16" Adjustable Height Coupler with Steel Booth (25,000 lb.)
- 12K Hydraulic Landing Gear with Manual Override
- 12v LED 24" 9K Lumen Exterior Scene Lights (4)
- 3/4" FlexCore™ Decking with Black Coin Rubber Floor Covering
- 3/8" FlexCore™ Sidewall Liner with .030 White Aluminum Covering
- White Aluminum Ceiling Liner
- Rear Ramp Door with Spring Assist
- 36" Aluminum Ramp Extension with Large Bumpers
- Premium Double Side Door with Pull-Out Step
- Cabinets: L-Shaped Base, Overhead and Generator Compartment (other configurations available at additional charge)
- Steel Car Hoist System with 36" Extension
- Upper Attic Deck with Ladder Access (Only available on 28' & 32' models)
- Generator Compartment with Access Door
- Air Compressor Prep Package — Hose, 4 Couplings and 120V Receptacle
- 120/240v 50 amp Motorbase Receptacle with Twist Lock Connect
- Battery Disconnect Switch
- 12v LED 36" Slim Line White Area/Accent Lights (8)
- 12v LED 6" Round Dome Lights (4)
- 16" OC Tube Crossmembers
- 16" OC Tube Vertical Posts
- 16" OC Tube Roof Structure
- D-Ring Tie-Downs with Welded Backer Plates (4)
- 3-Year Limited Warranty Program



Trailers shown may feature optional equipment available at additional cost.



www.wellscargo.com